

SmartRemote (Retail)



Product code: 77010600

Checking your Mastervolt product has never been easier

The SmartRemote completes any MasterBus system. With its good looks and compact size, the SmartRemote is ideal as a remote panel in entry level power systems or as a local device readout in larger systems. Applications include boats, vehicles and stationary systems.

Local device monitoring

Mastervolt products enable intelligent power systems with advanced multi-device monitoring and control. However, in situations where the local device readout is hard to reach or too limited, an entry-level color display for local device monitoring would be ideal. This is where the SmartRemote comes in.

Easy to use

The new SmartRemote single-device display is unique in many ways. It communicates with Mastervolt devices, shows key parameters, allows simple device settings and is fun to use. Checking your batteries, adjusting your shore fuse or controlling your Mastervolt charger/inverter has never been easier.

Easy to install

The SmartRemote display can be panel mounted or may be integrated into a Blue Sea Systems Custom 360 bezel. Connection is easy as 1-2-3: simply click the network cable into a Mastervolt device and off you go.

Affordable

The SmartRemote offers great value for money, having so many features in a compact and sturdy design, at a price which will surprise you.

Features

- Full color display for local device monitoring.
- Displays key parameters.
- Control key device functions.
- User adjustable power saving mode.
- MasterBus network compatible.
- Universal, easy mounting.
- Plug & Play – no configuration, no power supply needed.
- Blue Sea Systems Custom 360 integration.
- Support for English, Dutch, German, French, Spanish, Italian, Danish, Swedish, Norwegian, Finnish.

Supported products:

- Mac Plus, all models.
- Mass Chargers, all models.
- CombiMaster, all models.
- ChargeMaster Plus, all models.
- MLI Ultra 6000, MLI Ultra 5500, MLI Ultra 5000, MLI Ultra 3000, MLI Ultra 2750, MLI Ultra 2500, MLI Ultra 1250, MLI Ultra MKI.
- MasterShunt 500 CZone, MasterShunt 500.

Think Global, Act Local... Smart Remote!

Specifications

General specifications

Interfaces	MasterBus
Display/read-out	2.8 inch, 320 x 240 pixels, high colour
Mounting	panel mount (cutout: Ø 52 mm / 2 inch, 4 screws included); Blue Sea 360 panel mount (locking ring included)
Protection degree	IP20
Dimensions, hxxwxd	72 x 72 x 29.4 mm
	2.8 x 2.8 x 1.2 inch
Weight	0.075 kg
	0.2 lb
Delivered with	MasterBus cable (6 mtr), Mastervolt-CZone drop cable (1 mtr), manual

Technical specifications

Power consumption	Bus powered, < 160 mW (idle mode)
-------------------	-----------------------------------